





**D3150-1 GUIDE**

**RELEASED**  
2010-09-23  
*MP*



**NOTES:**

- 1) MATERIAL: AISI 303/304 STAINLESS STEEL SHEET, 0.125 (11 GAUGE) THICK  
ANNEALED 2B FINISH  
MIL-S-5059  
OR ASTM A240  
OR ASME SA240  
PER DART SPEC M303S11GA
- 2) FINISH: N/A
- 3) TOLERANCES: PER DART QSI 018 UNLESS OTHERWISE NOTED
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX
- 6) IDENTIFICATION: PER DART QSI 044 6.1
- 7) WEIGHT: 0.05 lbs
- 8) REPLACES PREMIER P/N B30-23000-171

C	RE-DESIGN; CHANGE MATERIAL TO 303 OR 304 WAS NORMALIZED 4130N BAR (ZN A8-1)	RF	10.09.15
B	ADD PART MARKING & NORMALIZED	RF	04.10.18
A	NEW ISSUE	RF	02.04.23
REV.	DESCRIPTION	BY	DATE
DESIGN	DS	<b>DART AEROSPACE LTD</b> HAWKESBURY, ONTARIO, CANADA	
DRAWN	RF		
CHECKED		DRAWING NO.	REV. C
MFG. APPR.		D3150	SHEET 1 OF 1
APPROVED		TITLE	SCALE
DE APPR.		GUIDE	NTS
DATE	10.09.15	COPYRIGHT © 2002 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	